

Georgia State Amendments to the International Plumbing Code

(2006 Edition)



Georgia Department of Community Affairs
Planning and Environmental Management Division
60 Executive Park South, N.E.
Atlanta, Georgia 30329-2231
(404) 679-3118
www.dca.state.ga.us

Revised January 1, 2008

GEORGIA STATE MINIMUM STANDARD PLUMBING CODE (INTERNATIONAL PLUMBING CODE WITH GEORGIA STATE AMENDMENTS)

The INTERNATIONAL PLUMBING CODE, 2006 Edition, published by the International Code Council, when used in conjunction with these Georgia State Amendments and the Georgia State Amendments adopted effective January 1 of 2007, shall constitute the official *Georgia State Minimum Standard Plumbing Code*.

GEORGIA STATE AMENDMENTS

CODE REFERENCE:

- (a) Replace all references to the ICC Electrical Code with references to the Georgia State Minimum Standard Electrical Code (National Electrical Code with Georgia State Amendments).
- (b) Replace all references to the *International Energy Conservation Code (IECC)* with references to the *Georgia State Minimum Standard Energy Code (IECC with Georgia State Supplements and Amendments)*. The *Georgia State Minimum Standard Energy Code* shall be used for efficiency and coefficient of performance ratings of plumbing equipment.

GEORGIA STATE MINIMUM REQUIREMENTS FOR BOILERS/WATER HEATERS AND PRESSURE VESSELS

The State's minimum requirements for boilers/water heaters and pressure vessels over 200,000 BTU/h (58.61 kW), 210 degrees Fahrenheit or 120 gallons capacity shall be established by O.C.G.A. Title 34, Chapter 11 and the Rules and Regulations of the Georgia Department of Labor.

*Revise the International Plumbing Code, 2006 Edition, as follows:

CHAPTER 10 TRAPS, INTERCEPTORS AND SEPARATORS

SECTION 1003 INTERCEPTORS AND SEPARATORS

*Add exception to Section 1003.4 'Oil separators required' of the Georgia Amendment revised January 1, 2007 to read as follows:

1003.4 Oil separators required.

Exception:

In elevator pits where oil containment complies with the Georgia Department of Labor Elevator Rules and Regulations, no additional oil separator shall be required. At repair garages, carwashing facilities, and factories where oily and flammable liquid wastes are produced, separators shall be installed into which all oil-bearing, grease-bearing or flammable wastes shall be discharged before emptying into the building drainage system or other point of disposal. (Effective January 1, 2008)

End of Amendments.