

# ICC 600-2014 errata STANDARD FOR RESIDENTIAL CONSTRUCTION IN HIGH- WIND REGIONS

(Portions of text and tables not shown are unaffected by the errata)

**FIRST PRINTING (Updated September 16, 2015)**

Page 66:

**TABLE 409(1)  
DIMENSIONAL REQUIREMENTS  
FOR WALLS<sup>a,b</sup>**

WALL TYPE AND NOMINAL THICKNESS	MAXIMUM WALL WEIGHT <sup>c</sup> (psf)	MINIMUM WIDTH OF VERTICAL CORES (inches)	MINIMUM THICKNESS OF VERTICAL CORES (inches)	MAXIMUM SPACING OF VERTICAL CORES (inches)	MAXIMUM SPACING OF HORIZONTAL CORES (inches)	MINIMUM WEB THICKNESS (inches)
4" flat	<del>4</del> <u>50</u>	N/A	N/A	N/A	N/A	N/A
6" flat	<del>6</del> <u>75</u>	N/A	N/A	N/A	N/A	N/A
8" flat	<del>9</del> <u>100</u>	N/A	N/A	N/A	N/A	N/A
10" flat	<del>11</del> <u>125</u>	N/A	N/A	N/A	N/A	N/A
6" waffle-grid	<del>5</del> <u>56</u>	6.25	5	12	16	2
8" waffle-grid	<del>7</del> <u>76</u>	7	7	12	16	2
6" screen-grid	<del>5</del> <u>53</u>	5.5	5.5	12	12	N/A

Page 68:

